

In the claims: Please change the claims as indicated.

---

1. (Currently amended) A method of deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the method comprising the steps of:

- a) recording ~~at least one~~ the first indication of the quality of the signal as received by the second communication device;
- b) providing a second indication of the quality of the signal based on the ~~at least one~~ first indication of the quality of the signal; and
- c) deciding to perform link adaptation based on the second indication of the quality of the signal.

2. (Original) The method of claim 1, wherein the first indication of the quality of the signal as received by the second communication device is either an SIR estimate, or an ACK/NACK signal, or an FER or BLER or corresponding statistic collected over a predetermined time period.

3. (Original) The method of claim 1, wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals.

4. (Original) The method of claim 3, wherein the decision

to perform link adaptation is based on whether the SIR target is to be changed to a value that is within some predetermined margin of a predetermined maximum or minimum SIR target.

5. (Original) The method of claim 3, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

6. (Original) The method of claim 3, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined fraction of a predetermined number the SIR target change commands are either to increase the SIR target or to decrease the SIR target.

7. (Currently amended) The method of claim 1, wherein the first communication device is selected from the group consisting of a mobile station and a base station and the second communication device is the other device in the group consisting of ~~a~~the mobile station and ~~a~~the base station.

8. (Currently amended) The method of claim 1, wherein either the first communication device or the second communication device perform one or more of the steps of recording ~~at least one~~ the first indication of the quality of the signal, providing a second indication of the quality of the signal, and deciding to perform link adaptation.

9. (Currently amended) The method of claim 1, wherein ~~an~~a radio network controller (RNC) performs one or more of the

steps of recording ~~at least one~~ the first indication of the quality of the signal, providing a second indication of the quality of the signal, and deciding to perform link adaptation.

10. (Original) The method of claim 1, wherein the signal for which the indication of the quality of the signal as received by the second communication device is used as a basis for a link adaptation decision is different from, but associated with, the signal for which the link adaptation decision is made.

11. (Currently amended) An apparatus for deciding whether to perform link adaptation for communication from a first communication device to a second communication device, the second communication device examining a signal received from the first communication device and providing a first indication of the quality of the signal as received by the second communication device, the apparatus comprising:

- a) means for recording ~~at least one~~ the first indication of the quality of the signal as received by the second communication device;
- b) means for providing a second indication of the quality of the signal based on the ~~at least one~~ first indication of the quality of the signal; and
- c) means for deciding to perform link adaptation based on the second indication of the quality of the signal.

12. (Original) The apparatus of claim 11, wherein the first indication of the quality of the signal as received by the second communication device is either an SIR estimate, or an ACK/NACK signal, or an FER or BLER or corresponding statistic collected over a predetermined time period.

13. (Original) The apparatus of claim 11, wherein the second indication of the quality of the signal as received by the second communication device is either an SIR target value, a changed SIR target value, an ACK/NACK signal, or a signal derived from a series of consecutive ACK/NACK signals.

14. (Original) The apparatus of claim 13, wherein the decision to perform link adaptation is based on whether the SIR target is to be changed to a value that is within some predetermined margin of a predetermined maximum or minimum SIR target.

15. (Original) The apparatus of claim 13, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined number of consecutive SIR target change commands are all either to increase the SIR target or to decrease the SIR target.

16. (Original) The apparatus of claim 13, wherein a succession of SIR target change commands are recorded, and further wherein the decision to perform link adaptation is based on whether a predetermined fraction of a predetermined number the SIR target change commands are either to increase the SIR target or to decrease the SIR target.

17. (Currently amended) The apparatus of claim 11, wherein the first communication device is selected from the group consisting of a mobile station and a base station and the second communication device is the other device in the group consisting of a-the mobile station and a-the base station.

18. (Currently amended) The apparatus of claim 11, wherein

the first communication device or the second communication device includes one or more of the means for recording at ~~least one~~ the first indication of the quality of the signal, means for providing a second indication of the quality of the signal, and means for deciding to perform link adaptation.

19. (Currently amended) The apparatus of claim 11, wherein ~~an~~ a radio network controller (RNC) includes one or more of the means for recording at ~~least one~~ the first indication of the quality of the signal, means for providing a second indication of the quality of the signal, and means for deciding to perform link adaptation.

20. (Original) The method of claim 11, wherein the signal for which the indication of the quality of the signal as received by the second communication device is used as a basis for a link adaptation decision is different from, but associated with, the signal for which the link adaptation decision is made.

---